


1/4 DIA. HOLE FOR
STD. 3 COND. PLUG



CUSTOMER DRAWING

NOTES:

1. JACK AND COVER ASSEMBLY, CAN AND HARDWARE ARE SHIPPED UNASSEMBLED.

THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT, INC., AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSE ONLY.

- UNLESS OTHERWISE SPECIFIED:
- 1 - DECIMAL DIMENSIONS ± .005
 - 2 - FRACTIONAL DIMENSIONS ± 1/64
 - 3 - ANGLES ± 1/2°
 - 4 - ALL DIA'S CONCENTRIC WITHIN .005 T.I.R.
 - 5 - ALL DIMENSIONS IN INCHES
 - 6 - FOR THREADS USE UNIFIED PLUG AND RING GAGES ONLY.
 - 7 - REMOVE ALL BURRS.
 - 8 - PART TO BE FABRICATED AS SPECIFIED. MAKE NO DIMENSIONAL ALLOWANCES FOR APPLIED FINISHES, I.E., PLATING, PAINTING, ETC.
 - 9 - HOLES ON SAME CENTERLINE MUST BE ALIGNED WITHIN ± .002
- DO NOT SCALE DRAWING

DRAWN BY <i>J.R.T.</i>	DATE 4-30-64	FINISH
CHECKED BY <i>[Signature]</i>	DATE 5-27-64	PER FINISH SPEC. NO.
APPROVED BY <i>LC</i>	DATE 6-26-64	MATERIAL
SCALE 2:1	FIRST USED ON	PER MAT. SPEC. NO.
NAME SHIELDED LITTEL		PART NO. CN-13B
ISSUE JAX		ISSUE B
SHEET		OF

REV	BY	DATE	REVISION
1	REDRAWN (S)	4-30-64	
2	A	5-27-64	WAS 2 COND. PLUG
3	B	6-26-64	CONDUCTORS
4	B	6-26-64	ECO # 23319