



NOTES:

1. MATERIALS:
EXTENSION JAX ASSEMBLY:
HOUSING & BUSHING - COPPER ALLOY, BRIGHT NICKEL
INSULATOR - THERMOPLASTIC, NATURAL
INSULATING WASHER - PHENOLIC
TIP AND RING SPRINGS - SPECIAL COPPER ALLOY, POLISHED
GROUND CLIP - SPECIAL COPPER ALLOY

FEMALE XLR SUB-ASSEMBLY:
SHELL - STAINLESS STEEL
INSULATOR - THERMOPLASTIC, GREEN
CONTACTS - SPECIAL COPPER ALLOY, SILVER PLATED
CONTACT FINGER - SPECIAL COPPER ALLOY, BRIGHT NICKEL
LATCH - ZINC ALLOY, NICKEL PLATED
SCREW - STAINLESS STEEL

ADAPTER HOUSING - ZINC ALLOY, SATIN NICKEL
TUBULAR INSULATOR - MYLAR
SCREWS - STEEL ALLOY, BRIGHT NICKEL

2. SHIPPED WIRED AND ASSEMBLED.
3. USES LEAD-FREE SOLDER.
4. THIS ASSEMBLY IS RoHS COMPLIANT.

CUSTOMER DRAWING

					<div>UNLESS OTHERWISE SPECIFIED</div> <div>1. ALL DIMENSIONS IN INCHES</div> <div>- TWO PLACE DECIMALS ±0.02</div> <div>- THREE PLACE DECIMALS ±0.005</div>	THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.															
						SIZE	WIDTH		MULT		LBS/M		TEMPER								
						FINISH						MATERIAL									
						SPEC No.						SPEC No.									
						FIRST USED ON				SCALE		<div>Switchcraft®</div>									
						*				1.5:1											
B	27584	10-8-15	TO	TJK		DATE DRAWN		BY	CHKD		APVD		SHEET 1 OF 1								
A	26232	2-15-07	TO	TJK		10-21-15		TO	TO		TJK										
									10-21-15		10-21-15										
REV	ECO NUMBER	DATE	BY	APVD		NAME						PART No.				REV					
REVISIONS					DO NOT SCALE DRAWING						FEMALE XLR TO Ø0.25 EXTENSION JACK WIRED, RoHS						383AWX				B