



NOTES:

1. MEETS SMPTE 2082-1
CHARACTERISTIC IMPEDANCE :75 OHMS
CONTACT RESISTANCE: 50 MILLIOHMS MAX.
2. MATERIAL:
PLUG: COPPER ALLOY, SILVER PLATED.
CONTACT: COPPER ALLOY, SILVER PLATED.
INSULATOR: TEFLON
OVERMOLD: THERMOPLASTIC ELASTOMER
3. THIS PRODUCT IS RoHS COMPLIANT.

CUSTOMER DRAWING

| | | | | | | | | | | | |
|-----------|--|--|--|--|--|-------|------|---------------|---------------------------------|----------|-----|
| | | | | | THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY. | | | | | | |
| | | | | | SIZE | WIDTH | MULT | LBS/M | TEMPER | | |
| | | | | | UNLESS OTHERWISE SPECIFIED | | | FINISH | | MATERIAL | |
| | | | | | 1. ALL DIMENSIONS IN INCHES [mm] | | | SPEC No. | | SPEC No. | |
| | | | | | - TWO PLACE DECIMALS ±0.02 [0.5] | | | FIRST USED ON | | SCALE | |
| | | | | | - THREE PLACE DECIMALS ±0.005 [0.13] | | | 5/01/17 | | 3:2 | |
| | | | | | DATE DRAWN | BY | CHKD | APVD | Switchcraft [®] | | |
| | | | | | 5/01/17 | PNK | PNK | SRC | | | |
| | | | | | NAME DUAL TERMINATED PLUG | | | | PART No. | | REV |
| | | | | | UHD MICRO, OVERMOLDED, RoHS | | | | VMMTPUHD | | A |
| REVISIONS | | | | | DO NOT SCALE DRAWING | | | | | | |