



DIMENSIONS SHOWN ARE REFERENCE ONLY

NOTES:

1. MEETS SMPTE 2082-1  
CHARACTERISTIC IMPEDANCE :75 OHMS  
CONTACT RESISTANCE: 50 MILLIOHMS MAX.
2. WIRING: CENTER CONTACT TO CENTER CONTACTS  
GROUND SLEEVE TO GROUND SLEEVE
3. MATERIAL:  
PLUG: COPPER ALLOY, NICKEL PLATED.  
CONTACT: COPPER ALLOY, GOLD PLATED.  
INSULATOR: TEFLON  
OVERMOLD: THERMOPLASTIC ELASTOMER
4. THIS PRODUCT IS RoHS COMPLIANT.

**CUSTOMER DRAWING**

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.						
					SIZE	WIDTH	MULT	LBS/M	TEMPER		
					UNLESS OTHERWISE SPECIFIED			FINISH			
					1. ALL DIMENSIONS IN INCHES [mm]			MATERIAL			
					- TWO PLACE DECIMALS ±0.02 [0.5]			SPEC No.			
					- THREE PLACE DECIMALS ±0.005 [0.13]			FIRST USED ON			
								SCALE			
								3:2			
					DATE DRAWN	BY	CHKD	APVD	<b>Switchcraft</b> <sup>®</sup>		
					5/01/17	PNK	PNK	SRC			
0A	PDR 16006	5/01/17	PNK	SRC				SHEET 1 OF 1			
REV	ECO NUMBER	DATE	BY	APVD	NAME			PART No.	REV		
REVISIONS					DO NOT SCALE DRAWING			DUAL TERMINATED PLUG UHD MICRO, OVERMOLDED, RoHS		VMMTPUHD	0A