


S'Y P/N	CONTACT QTY.	KEY STYLE
0-5PG-300	5 - #26	A-KEY
0-6PG-300	6 - #26	B-KEY
0-7PG-300	7 - #26	A-KEY

└──NUMBER OF CONTACTS



|--|

ι.	PAK	07/28/10	DRAWING CREATED PER DOR 09-E168CS; ADDED 5-POS. ASSY.				
V.	INIT.	DATE	DESCRIPTION				
ALL INFORMATION ILLUSTRATED IS THE PROPERTY OF "CONXALL CORPORATION." UNAUTHORIZED		orig. drawn PAK	IBY: I	date: 08/24/09			
DUPLICATION OR DISTRIBUTION OF THIS DOCUMENT IS PROHIBITED.		CHECKED BY:					
ALL UNITS ARE IN FEET, INCHES, FRACTION OF INCHES AND DECIMALS.					601 E. WILDWOOD VILLA PARK, IL 60181		
		APPROVED BY:			TITLE: PANEL CONNECTOR ASSEMBLY		
UNLESS OTHERWISE SPECIFIED					#26 PIN CONTACTS, CRIMP		
3 PLACE DECIMALS ANGLES ±1° FRACTIONS ±1/1	CIMALS ±.005 ES ±1°	scale NTS	size B	sheet 1 OF 1	MICRO-CON-X, A-KEY & B-KEY customer: STANDARD PRODUCT		
<ul> <li>CRITICAL CHARACTERISTIC</li> <li>FLAG PER SPEC. XXXX</li> </ul>		file: 17980-XF	G-30	DIRECTORY: 0 SLW	NUMBER: 17980-XPG-300	REV A	