ASS'Y P/N "X" DIM. CARA168804P03990 3 FT. 3 1/2 IN. ± 2 IN. [1M] CARA168804P07990 6 FT. 7 IN. ± 2 IN. [2M] FINISHED CABLE ASSEMBLY 3 FEET OR SHORTER TO BE BUNDLED.
 FINISHED CABLE ASSEMBLY OVER 3 FEET TO BE COILED.
 OVERMOLD BOOT MATERIAL: PVC, BLACK
 ELECTRICAL TEST: 100% CONTINUITY CARA168804P19790 16 FT. 5 IN. ± 4 IN. [5M] CARA168804P39490 32 FT. 9 3/4 IN. ± 8 IN. [10M] CARA168804PXXX90 ALL DIMENSIONS ARE REFERENCE ONLY EXCEPT WHEN NOTED WITH **TOLERANCE** -CABLE LENGTH IN "INCHES" "X" DIM. CUSTOMER PRINT [33.1mm] CUT BLUNT  $\langle B \rangle$ 1.490 IN. [37.8mm] RIGHT ANGLE FLEX OVERMOLDED CABLE CONNECTOR, MALE (4)-#22 AWG CONDUCTORS JACKET: PVC, BLACK 0.195 O.D. REF. MAT'L: NYLON, BLACK
(4) #22 PIN CONTACTS
MAT'L: GOLD PLATED COPPER ALLOY
CXA #16880-4PG 300 V OIL RESISTANT COUPLING RING MAT'L: NYLON, BLACK O-RING MAT'L: RUBBER, BLACK CARA168804PXXX90 MASTER **CUSTOMER APPROVAL** THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION PROPRIETARY TO CONXALL CHANGED TO FLEX OVERMOLD, UPDATED CONNECTOR DIMENSIONS ΑN 03-26-21 CORPORATION. ANY REPRODUCTION, DISCLOSURE, OR USE OF THIS ΑN 09-17-19 DRAWING CREATED PER DOR 19-SQ104237JS DOCUMENT /INFORMATION IS EXPRESSLY PROHIBITED UNLESS AUTHORIZED IN REV. INIT. DATE DESCRIPTION WRITING BY CONXALL CORPORATION. 08-20-19 CHECKED BY: APPROVED BY: 601 E. WILDWOOD VILLA PARK, IL 60181 DATE: \_ CABLE ASSEMBLY WIRE COLOR CODE, END "A" (4) #22 PIN CONTACTS MICRO-CON-X, R.ANGLE STANDARD PRODUCT POS. 1 POS. 2 POS. 3 POS. 4 SCALE NTS SHEET 1 OF 1 DIMENSIONS IN BRACKET [ ] ARE METRIC. **ROHS COMPLIANT** WHT BLU BRN PART NUMBER: CARA168804PXXX90