



DIE CLOSURES		
SEL NO	ØGO	ØNO-GO
1	0.0280	0.0330
2	0.0320	0.0370
3	0.0360	0.0410
4	0.0390	0.0440
5	0.0450	0.0500
6	0.0520	0.0570
7	0.0590	0.0640
8	0.0680	0.0730
USE GAGE G125 AT SELECTOR SETTING 4		

NOTES:

1. TOOL TO BE USED WITH POSITIONER EN2POS20L.
2. DMC TOOL FRAME NUMBER WA27F, DMC POSITIONER NUMBER TP1693.

CUSTOMER DRAWING

					THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.						
					SIZE	WIDTH	MULT	LBS/M	TEMPER		
					UNLESS OTHERWISE SPECIFIED			FINISH		MATERIAL	
					1. ALL DIMENSIONS IN INCHES			SPEC No.		SPEC No.	
					- TWO PLACE DECIMALS ±0.02			FIRST USED ON		SCALE	
					- THREE PLACE DECIMALS ±0.005			NOT TO SCALE		Switchcraft®	
A	27372	10/03/14	PC	TJK	DATE DRAWN	BY	CHKD	APVD			
REV	ECO NUMBER	DATE	BY	APVD	9/26/12	PNK	PNK	SRC			
REVISIONS					DO NOT SCALE DRAWING					SHEET 1 OF 1	
					NAME PNEUMATIC CRIMP TOOL					PART No.	REV
					EN2 SERIES #20 AND #22 CONTACTS					EN2CRAUTOL	A

