

RCA AND RCA WIRING CHART								
JACKET	H.S. TUBING	END "A" RCA PLUG			END "B" RCA PLUG			
COLOR	MARKING	RED	BLACK	BARE	RED	BLACK	BARE	
BROWN	CHANNEL 1	TIP	RING	SLEEVE	TIP	RING	SLEEVE	
RED	CHANNEL 2	TIP	RING	SLEEVE	TIP	RING	SLEEVE	
ORANGE	CHANNEL 3	TIP	RING	SLEEVE	TIP	RING	SLEEVE	
YELLOW	CHANNEL 4	TIP	RING	SLEEVE	TIP	RING	SLEEVE	
GREEN	CHANNEL 5	TIP	RING	SLEEVE	TIP	RING	SLEEVE	
BLUE	CHANNEL 6	TIP	RING	SLEEVE	TIP	RING	SLEEVE	
PURPLE	CHANNEL 7	TIP	RING	SLEEVE	TIP	RING	SLEEVE	
GRAY	CHANNEL 8	TIP	RING	SLEEVE	TIP	RING	SLEEVE	

PART NUMBER	CABLE LENGTH " <b>X</b> "	RCA FINISH			
RCA05RCA	5.00 FT +/- 1.50 IN	NICKEL HANDLE, NICKEL PIN			
RCA10RCA	10.00 FT +/- 1.50 IN	NICKEL HANDLE, NICKEL PIN			
RCA05RCAB	5.00 FT +/- 1.50 IN	BLACK HANDLE, GOLD PIN			
RCA10RCAB	10.00 FT +/- 1.50 IN	BLACK HANDLE, GOLD PIN			

## **CUSTOMER DRAWING**

## NOTES: $\langle B \rangle$

- 1. CABLE BREAKOUT LENGTH IS 18 +/- 0.75 IN.
- 2. CABLE IS SHIPPED COILED AND PACKAGED IN A BAG.
- 3. MATERIALS:

WASHER - PHENOLIC CENTER PIN - COPPER ALLOY, SEE TABLE
PLUG HOUSING - COPPER ALLOY, SEE TABLE
CLAMP TERMINAL - STEEL, ELECTRO-TINNED
HANDLE - COPPER ALLOY CABLE - COPPER, THERMOPLASTIC

4. THIS PRODUCT IS RoHS COMPLIANT.

	1. ALL DIMENSIONS IN INCHES - TWO PLACE DECIMALS ±0.02	SIZE FINISH SPEC No.	WI	IDTH	MULT	MATERIAL	LBS/M	TEMPER	
		1	-		<u> </u>	MATERIAL	L		
	- TWO PLACE DECIMALS +0.02	SPEC No.							
		SPEC No.				SPEC No.			
	- THREE PLACE DECIMALS ±0.005	FIRST US	FIRST USED ON		CALE 1:2	  Swifehe			F
B 26637 10/11/10 RS 1	(	DATE DRAWN	BY	CHKD	APVD			الةلاقال	ШL
A 25983 10/30/08 RS 7	<u> </u>	4/14/08	JGK	RS	TJK				
A 25983 10/30/08 RS 1	<u> </u>			12/21/10	12/22/10		SHEET 1	OF 1	
REV ECO NUMBER DATE BY A	'D	NAME				PART No.			RE
REVISIONS	DO NOT SCALE DRAWING	RCA PLUC	RCA PLUG TO RCA PLUG, RoHS			RCARCA SERIES			<u>E</u>

SolidWorks CAD File B