

ASS'Y P/N		I.D. FOR CABLE		
SF3282-XPG-5	20	Ø0.200		
SF3282-XPG-5	30	Ø0.300		
SF3282- <u>X</u> PG-540		Ø0.400		
		NTACTS: 2 to 12		

A	MA	04-28-20	RELEAS	RELEASED PER PDR 15019-1				
A	JGK	03/31/20	CREATED FOR PDR#15019.					
EV.	INIT.	DATE	DESCRIPTION					
ALL INFORMATION ILLUSTRATED IS THE PROPERTY OF "CONXALL CORPORATION." UNAUTHORIZED DUPLICATION OR DISTRIBUTION OF THIS DOCUMENT IS PROHIBITED.			ORIG. DRAWN JGK CHECKED BY		date: 03/31/20	conxall		
ALL UNITS ARE IN FEET,						601 E. WILDWOOD VILLA PARK, IL 60181		
INCHES, FRACTION OF INCHES AND DECIMALS. UNLESS OTHERWISE SPECIFIED 3 PLACE DECIMALS ± 005 ANGLES ± 1' FRACTIONS ± 1/16 = CRITICAL CHARACTERISTIC FLAG PER SPEC. XXXX		APPROVED BY:			TITLE: CONNECTOR ASSEMBLY KIT (2-12) #20 PIN CONTACTS			
		scale NTS	size B	sheet 1 OF 1	SHIELDED MULTI-CON-X customer: STANDARD PRODUCT			
		CHARACTERISTIC	FILE: SF3282-XPG-	5XX_CD	DIRECTORY: SLW	PART NUMBER: SF3282-XPG-5XX	rev A	