

POSITIONS											
POS 4	POS 5	POS 6	POS 7	POS 8	POS 9	POS 10	POS 11	POS 12			
	OPEN			OPEN							
OPEN		OPEN	OPEN		OPEN						
OPEN	OPEN		OPEN OPEN								
OPEN		OPEN	OPEN OPEN								
OPEN	OPEN	OPEN	OPEN	OPEN	OPEN						
OPEN	OPEN	OPEN	OPEN	N OPEN OPEN							
OPEN	OPEN	OPEN	OPEN	OPEN	OPEN	OPEN					
OPEN	OPEN	OPEN	OPEN	OPEN	OPEN	OPEN	OPEN				
OPEN	OPEN	OPEN	OPEN	OPEN	OPEN	OPEN	OPEN	OPEN			

_														
3	MA	10-09-19	INSERT MATERIAL WAS NYLON, BLACK PER ECR 9439											
F	AN	03-19-19	DIM197 WAS .202, .175 WAS 0176. PER ECR 9338											
E	JD	05-30-17	REVISED SHIPPING/PACKAGING NOTES PER ECR'S 8587 & 8898											
D	PD	07-12-11	ADDED F	ТΧТ	JRE NO. TO	NOTE 3. PER ECR 7915								
С	ΒZ	04-11-11	ADDED BAG P/N TO NOTE 1 PER ECR 7838											
В	DT	07-21-08	REPLACED MULTI-SHIELD-CON WITH SHIELDED MULTI-CON-X PER ECR 6903											
A	SXL	02-15-07	DRAWING CREATED PER DOR 07-E149JC											
EV.	INIT.	DATE	DESCRIPTION											
ALL INFORMATION ILLUSTRATED IS THE PROPERTY OF "CONXALL CORPORATION" UNAUTHORIZED DUPLICATION OR DISTRIBUTION OF THIS DOCUMENT IS PROHIBITED.			ORIG. DRAWN BY: DATE: S.X.LOU 02-15-07 CHECKED BY:											
ALL UNITS ARE IN FEET, INCHES, FRACTION OF INCHES AND DECIMALS.			APPROVED BY SCALE NTS	size B	sheet 1 OF 1	TITLE: SHIELDED PANEL ASS'Y (4-12) #20 PC TAIL PIN CONTACTS SHIELDED MULTI-CON-X customer: STANDARD PRODUCT								
>	= CRITICAL FLAG PER S	CHARACTERISTIC PEC. XXXX	file: SF4281-XXE	PG-3E	DIRECTORY:	NUMBER: SF4281-XXEPG-3ES								