

POSITION								
POS 4	POS 5	POS 6	POS 7	POS 8	POS 9	POS 10	POS 11	POS 12
	OPEN			OPEN				
OPEN		OPEN	OPEN		OPEN			
OPEN	OPEN		OPEN	OPEN				
OPEN		OPEN	OPEN		OPEN			
OPEN	OPEN	OPEN	OPEN	OPEN	OPEN			
OPEN	OPEN	OPEN	OPEN	OPEN	OPEN			
OPEN	OPEN	OPEN	OPEN	OPEN	OPEN	OPEN		
OPEN	OPEN	OPEN	OPEN	OPEN	OPEN	OPEN	OPEN	
OPEN	OPEN	OPEN	OPEN	OPEN	OPEN	OPEN	OPEN	OPEN

[&]quot;---" HALF CLOSED FROM MATING END

ESS .)										
G	MA	10-10-19	MALE INSERT MAT'L WAS NYLON, BLACK PER ECR 9439							
F	AN	03-20-19	DIM. 0.266 W	/AS 0.271, 0. ⁻	164 WAS 0.169, ADDED N OTE 7. PER ECR 9338					
E	JD	06-20-17	UPDATED SHIPPING/PACKAGING NOTES AND VIEWS AND ADDED NOTE FOR SOLDER CUP ORIENTATION PER ECR 8380							
D	AN	01-11-13	UPDATED N	IANUFACTU	RING NOTE PER ECR 8264					
с	AN	11-22-11	UPDATED N PER ECR 80		ED ALL POSITIONS TOCHART.					
В	DT	07-21-08	REPLACED MULTI-SHIELD-CON WITH SHIELDED MULTI-CON-X PER ECR 690							
	RCS	10-11-05	FILE NO.WAS SF4282-12PG-3ES							
А	RCS	01-14-04	DRAWING CREATED PER DOR #03-9008KN							
REV.	INIT.	DATE	DESCRIPTION							
ALL INFORMATION ILLUSTRATED IS THE PROPERITY OF "CONXALL CORPORATION." UNAUTHORIZED DUPLICATION OR DISTRIBUTION OF THIS DOCUMENT IS PROHIBIED.			ORIG. DRAWN BY: RCS CHECKED BY:	date: 01-14-04	601 E. WILDWOOD VILLA PARK, IL 60181					
ALL UNITS ARE IN FEET, INCHES, FRACTION OF INCHES AND DECIMALS.		APPROVED BY: SCALE SIZE	SHEET	TITLE: SHIELDED PANEL ASS'Y (4-12) #20 PIN CONTACTS SHIELDED MULTI-CON-X						
= CRITICAL CHARACTERISTIC FLAG PER SPEC. XXXX			NTS B FILE: SF4282-XXEPG-3	1 OF 1 DIRECTORY: ES SLW		ev G				